

Product Name: PRO-3000 Color-Tinted Silicone Revision Date: May 1, 2017

## 1. Product & Company Information

Commercial Product Name: PRO 3000 COLOR-TINTED SILICONE

Product Classification: Silicone Sealant

Manufacturer: Distributor:

 Silco Inc.
 Design Imaging, LLC

 7635 St. Clair Avenue
 1170 Industrial Park Rd.

 Mentor, OH 44060
 Orem, UT 84057

 Phone: 440.975.8886
 Phone: 844.328.3331

General Description: Silicone elastomer

Physical Form: Paste Color: Trans Beige Odor: Acetic acid odor

NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

#### 2. Hazards Identification

Physical Hazards: Not classified

**Health Hazards:** Reproductive toxicity (fertility) Category 2

Environmental Hazards: Not classified OSHA Defined Hazards: Not classified

• Hazards not stated here are "Not Classified", "Not Applicable" or "Classification not possible".

**GHS Label Elements** 

Signal Word: Warning

Hazard(S) not Otherwise

the conditions of use:





**Hazard Statement:** Suspected of damaging fertility. May cause eye/lung/skin irritation.

Precautionary Statement: Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood

Prevention: Wear protective gloves / protective clothing / eye protection / face protection. Wash well after handling.

Contaminated work clothing should not be allowed out of work place.

Response: SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention / advice. Get

medical attention / advice if you feel unwell.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritant persists get medical attention / advice.

If exposed or concerned: get medical attention or advice. Take off contaminated clothing and wash it before

reuse.

Storage: Store locked up.

Disposal: Disposal of contents / container in accordance with local / regional /state / federal and international regulations.

None known

classified (HNOC):
Supplemental Information:
None known.

Substance(s) formed under

This product reacts with water, moisture or humid air to evolve following compounds: Acetic acid

The following material is embedded in the product and not available as respirable dusts. When used as intended

or as supplied, the product will not pose hazards. Titanium oxide.

HMIS (Ratings): Health: 1

Flammability: 1 Physical hazard: 0

### 3. Composition / Ingredients

#### Mixtures - Hazardous Ingredients

i nazaradas ingredients		
Chemical Name	CAS Number	%
Ethyltriacetoxysilane	17689-77-9	1 – 5
Methylacetoxysilane	4253-34-3	1 – 5
Titanium oxide	13463-67-7	< 1
Distillates (petroleum), hydrotreated middle	64742-46-7	1 – 7
Octamethylcyclotetrasiloxane (impurity)	556-67-2	< 1

PerformanceProAdhesives.com Page 1 of 6



## 4. First Aid Measures

Inhalation: Remove to fresh air. Call a physician if symptoms develop or persist.

Skin Contact: Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on unaffected skin. If skin

irritation or rash occurs: get medical attention / advice. Take off contaminated clothing and wash before use.

Eyes Contact: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if irritation developed or persists.

**Ingestion:** Wash out mouth. Get medical attention immediately.

Most Important symptoms / effects, acute and delayed:

Direct contact with eyes may cause temporary irritation.

Indication of immediate Medical attention and Special treatment Needed: Treat Symptomatically.

General Information: If exposed or concerned: Get medical advice / attention. Ensure that medical personnel are aware materials involved and

take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire Fighting Measures

Suitable extinguishing media: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2

Unsuitable extinguishing media: None known.

Specific hazards arising from the chemical:

By heating and fire, harmful vapors / gases may be formed.

Specific protective equipment and precautions for firefighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves,

rubber boots and self-contained breathing apparatus.

Fire Fighting equipment / Instructions: Move containers from fire area if you can do so without risk.

**General fire hazards:** No unusual fire or explosion hazards noted.

#### 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch or walk through spilled material. Ensure adequate ventilation. Wear

be contained. Do not touch or waik through spilled material. Ensure adequate ventilation, wear

appropriate personal protective equipment.

Methods and materials for containment and cleaning up:

Eliminate sources of ignition.

**Large Spills:** Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up product and

place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth). Clean surface thoroughly to remove

residual contamination. Never return spills in original containers for reuse.

Environmental precautions: Prevent further leakage or spillage if safe to do so.

## 7. Handling & Storage

**Precaution for safe handling:**Provide adequate ventilation. Use care in handling/storage. Obtain special instructions before use. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Pregnant

and breastfeeding women must not handle this product. Do not breathe mist or vapor. Avoid contact with eyes.

Avoid contact with skin. Avoid long term exposure.

Conditions for safe storage, Including any incompatibilities:

Stored locked up. Keep container tightly closed. Keep out of reach of children. Store in a cool dry place out of direct sunlight. Keep in original container.

PerformanceProAdhesives.com Page 2 of 6



## 8. Exposure Controls / Personal Protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components CAS# Value Type 13463-67-7 Titanium oxide PFI 15 mg/m3

Decomposition CAS# Value Type Distillates (petroleum) TWA (Mist) 64742-46-7 5 mg/m3

hydrotreated middle

Acetic acid 64-19-7 PEL 25 mg/m3 10 ppm

**US. ACGIH Threshold Limit Values Components** Components CAS# Value Type

Titanium oxide 13463-67-7 TWA 10 mg/m3

Type Decomposition CAS# Value Acetic acid 64-19-7 STEL 15 ppm **TWA** 10 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

CAS# Decomposition **Type** Value Acetic acid 64-19-7 STEL 37 mg/m3 15 ppm

**TWA** 25 mg/m3 10 ppm

Distillates (petroleum) 64742-46-7 TWA (Mist) 5mg/m3 hydrotreated middle ST (Mist) 10mg/m3

Biological limit values: No biological exposure limits for the ingredient(s).

Provide adequate general and local exhaust. Provide eyewash station. Pay attention to ventilation such as local Appropriate engineering controls:

exhaust, mechanical and or / door open for at least 24 hours after applications.

Individual protection measures such as personal protective equipment.

Eye / Face protection: Tightly sealed safety glasses according to EN 166.

Skin / Hand protection: Wear protective gloves.

Other: Wear suitable protective clothing.

Respiratory protection: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

Avoid contact with eyes. Avoid contact with skin. When using, do not eat, drink or smoke. Keep away from food **General Hygiene Considerations:** 

or drink. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the work place. Handle in accordance with good industrial hygiene and safety

practice.

## 9. Physical / Chemical Characteristics

**Appearance** 

Form: Paste Color: Trans Beige Odor: Acetic acid odor Not available **Odor Threshold:** Not available Melting point / freezing point: Not available Initial boiling point and Not available

boiling range:

Flash Point: 141.8 oF (> 96 0 C) Closed cup

Evaporative rate: < 1 (Butyl Acetate = 1) Flammability (solid, gas): Not applicable

Upper / Lower flammability or explosive limits: Flammability limit - lower (%): No data Flammability limit - upper (%): No data Explosive limit - Lower (%): Not available Explosive limit - Upper (%): Not available Vapor pressure: Negligible (250 C) Vapor density: > 1 (air=1) Relative density: 1.04 (25 0 C) Solubility (water): Not soluble **VOC Content:** 30 grams per liter Partition coefficient: Not applicable

(n-octanol / water) Auto-ignition temperature: No data **Decomposition temperature:** Not available Viscosity: Not applicable Molecular weight: Not applicable

Page 3 of 6 PerformanceProAdhesives.com



## 10. Stability & Reactivity

Reactivity: No hazardous reaction known under normal conditions of use, storage and transport.

Chemical stability: Stable at normal conditions.

Possibility of hazardous Reactions: Hazardous polymerization does not occur.

Conditions to avoid: None known.

**Incompatible materials:** Strong oxidizing agents. Water and moisture.

Hazardous decomposition products: This product reacts with water, moisture, or humid air to evolve following compounds. Acetic acid.

Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon dioxides and traces of incompletely burned carbon compounds. Silicon dioxide.

Formaldehyde.

### 11. Toxicological Information

Information on likely routes of exposure

Ingestion:Expected to be a low ingestion hazard.Inhalation:Prolonged inhalation may be harmful.

**Skin contact:**No adverse effects due to skin contact are expected. **Eye contact:**Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical, and

toxicological characteristics: Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity
Toxicological data

Decomposition CAS # Species Test Results
Acetic acid 64-19-7

Acute
Dermal
LD50

LC 50

LD50 Rabbit 1060 mg/kg Inhalation

Guinea Pig 5000 ppm, 1 hours
Mouse 5620 ppm, 1 hours
Rat 11.4 mg/l, 4hours

 Oral
 Mouse
 4960 mg/kg

 LD50
 Rabbit
 1200 mg/kg

 Rat
 3.31 g/kg

Distillates (petroleum) hydrotreated middle

 Oral
 Rat
 > 5,000 mg/kg

 Inhalation
 LC 50
 Rat
 1.78 mg/l. 4 hg

 $\begin{array}{cccc} \text{LC 50} & & \text{Rat} & & 1.78 \text{ mg/l}, 4 \text{ hours} \\ \text{Dermal} & & \text{Rat} & & > 2,000 \text{ mg/kg} \end{array}$ 

Skin corrosion / irritation: Causes severe skin burns and eye damage. (Acetic acid)
Skin-Rabbit: 500 mg/24hr.MILD (Octamethylcyclotetrasiloxane)

Serious eye damage/eye irritation: Causes serious eye damage. (Acetic acid)

Eye - Rabbit: MILD (Octamethylcycotetrasiloxane)

Respiratory Sensitization: Not available.

Skin Sensitization: No evidence of sensitization (Octamethylcycotetrasiloxane)

Germ Cell Mutagenicity: Negative (Bacteria) (Octamethylcycotetrasiloxane)

Carcinogenicity: The following material is embedded in the product and not available as respirable dusts. When used as

intended or as supplied, the product will not pose hazards. Titanium oxide.

IARC Monographs, Overall Evaluation of Carcinogenicity: Titanium oxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Not listed

Substances (29 CFR 1910.1001-1050):

PerformanceProAdhesives.com Page 4 of 6



### 11. Toxicological Information (cont.)

Reproductive Toxicity: Octamethylcyclotetrasiloxane administered to rats by whole body inhalation at concentrations of 500 and 700

ppm for 70 days prior to mating, through mating, gestation and lactation resulted in decreases in live litter size. Additionally, increases in the incidence of deliveries of offspring extending over an unusually long time period (dystocia) were observed at these concentrations. Statistically significant alterations in these parameters were not observed in the lower concentrations evaluated (300 and 70 ppm). In a previous range-finding study, rats exposed to vapor concentrations of 700 ppm had decreases in the number of implantation sites and live litter

size. The significance of these findings to humans is not known. (Octamethylcyclotetrasiloxane)

Specific target organ toxicity – single exposure:

Not available

Specific target organ toxicity – repeated exposure:

Repeated inhalation or oral exposure of mice and rats to Octamethylcycotetrasiloxane produced an increase in liver size. No gross histopathological or significant clinical chemistry effects were observed. An increase in liver metabolizing enzymes, as well as a transient increase in the number of normal cells (hyperplasia) followed by an increase in cell size (hypertrophy) were determined to be the underlying causes of the liver enlargement. The biochemical mechanisms producing these effects are highly sensitive in rodents, while similar mechanisms in humans are insensitive. A two year combined chronic and carcinogenicity assay was conducted on Octamethylcyclotetrasiloxane. Rats were exposed by whole-body vapor inhalation 6hrs /day, 5 days a week for up to 104 weeks to 0, 10, 30, 150 or 700 ppm of Octamethylcyclotetrasiloxane. The increase in incidence of (uterine) endometrial cell hyperplasia and uterine adenomas (benign tumors) were observed in female rats at 700 ppm. Since these effects only occurred at 700 ppm, a level that greatly exceeds typical workplace or consumer exposure, it is unlikely that industrial, commercial or consumer uses of products containing Octamethylcyclotetrasiloxane would result in a significant risk to humans. (Octamethylcyclotetrasiloxane)

Aspiration hazard: The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it

causes a human aspiration toxicity hazard. Distillates (petroleum), hydrotreated middle

Chronic effects: Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Further Information: This product reacts with water, moisture or humid air to evolve following compounds: Acetic acid.

#### 12. Ecological Considerations

**Ecotoxicity** 

Octamethylcyclotetrasiloxane: May cause long lasting harmful effects to aquatic life.

Components

Titanium oxide (CAS 13463-67-7)

Species

Test Results

Aquatic

Crustacea EC50 Water Flea (Daphnia magna) > 1000 mg/l, 48 hours Fish LC50 Mummichog (Fundulus Heteroclitus) > 1000 mg/l, 96 hours

Decomposition

Acetic acid (CAS 64-19-7)

Aquatic

Crustacea EC50 Water flea (Daphnia Magna) 65 mg/l, 48 hours

Fish LC50 Bluegill (Leponis Macrochirus) 75mg/l, 96 hours

Persistence and degradability: Not available.

Bioaccumulative potential: Bio concentration Factor (BCF) / (Flathead minnow): 12400 Octamethylcyclotetrasiloxane.

Mobility in Soil:Not available.Other adverse effects:Not available

#### 13. Disposal Considerations

Can be land-filled for cured product or burned in a chemical incinerator equipped with an afterburner and scrubber. Do not dispose the emptied container unlawfully. Observe all federal, state & local laws.

## 14. Transportation Information

**DOT:** Not regulated as dangerous good. **IATA:** Not regulated as dangerous good. **IMDG:** Not regulated as dangerous good.

Transport in bulk according to Annex II of MARPDL 73/78 and the IBC Code: This product is not intended to be transported in bulk.

PerformanceProAdhesives.com Page 5 of 6



## 15. Regulatory Information

**US** federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed

# SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) SARA 313 (TRI reporting)

#### **US State Regulations**

Massachusetts: Substance List: Titanium oxide (CAS 13463-67-7)

#### New Jersey Worker and Community Right to Know Act:

Titanium oxide (CAS 13463-67-7)

#### Pennsylvania Worker and Community Right to Know Act:

Titanium oxide (CAS 13463-67-7)

#### **Rhode Island RTK:**

Not regulated.

#### California Proposition 65:

The following material is embedded in the product and not available as respirable dusts. When used as intended or as supplied, the product will not pose hazards.

#### US California Proposition 65 - CRT: Listed date / Carcinogenic substance

Titanium oxide (CAS 13463-67-7) Listed: September 2, 2011

International Inventories		
Country(s) or region Australia	Inventory Name Australian Inventory of Chemical Substances (AICS)	On Inventory (yes/no)* Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non Domestic Substances (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemicals	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
United States	Toxic Substances Control Act (TSCA) Inventory	Yes

### 16. Other Information

#### Prepared by: Design Imaging, LLC

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

PerformanceProAdhesives.com Page 6 of 6